

MID-RISE LIFT

Engineered to perform... Built to last!

The mid-rise lift is an excellent choice for low ceilings or adding a bay for seasonal increases in business. Provides good working height for tires, brakes and body repairs.



Shown: 6000 MRL
6,000 lbs. capacity

Model 6000MRL

- Full 6,000 lbs. capacity
- Portable, easy to move
- Two hydraulic cylinders
- Fast operation: 20-30 seconds
- Multiple locking positions
- Truck adapters included

Engineering Excellence

Forward's U.S. engineers have over 29 years of combined experience designing automotive lifts for service and repair shops. Forward's philosophy is to own our designs rather than use someone else's off the shelf product.

Product Integrity

21st century design tools allow us to create, control and validate our designs to ensure maximum performance. Forward lifts are thoroughly tested to meet quality and durability standards. All product families are proof load tested to 1½ times rated capacity and rigorously cycle tested.

Specifications	6000MRL
Capacity	6,000 lbs. (2722kg)
Rise	52"
Length	83"
Width	41"
Fully Lowered	5"
Motor	110 volt or 220 volt
Shipping Weight	1,000 lbs. (454kg)

Specifications subject to change without notice or liability.

FORWARD
LIFT

LOW-RISE LIFTS

Features


- 10,000 lbs. capacity or 7,000 lbs. capacity
- Drive-over ramps and side rails provide the width to support wider vehicles during approach
- Dual lifting cylinders provide the power required to lift a 10,000 lbs. vehicle
- The TL10 comes with four 3-position adapters, four 3" rubber blocks and four 1-1/2" rubber blocks for added height.



Shown: TL10111000
10,000 lbs. capacity



- The TL07 comes with four 3" rubber blocks and four 1-1/2" rubber blocks.



Shown: TL07111000
7,000 lbs. capacity

Specifications	TL10	TL07
Capacity	10,000 lbs.	7,000 lbs.
Rise High Step	30-5/16"	N/A
Rise Mid Step	28-5/16"	N/A
Rise Low Step	26-5/16"	N/A
Rise Tall Pad	24-3/4"	24-3/4"
Rise Short Pad	23-1/4"	23-1/4"
Rise Flat	21-3/4"	21-3/4"
Length Overall	90-1/2"	90-1/2"
Width Overall	78-1/2"	78-1/2"
Width Between Platforms	22-3/4"	22-3/4"
Length of Platforms	51-1/4"	51-1/4"
Length of Pad	17"	17"
Outside Width of Platforms	70-3/4"	70-3/4"
Horizontal Movement (during rise)	16"	16"
Collapsed Height	4"	4"
Locking Leg Heights	13-3/8"	13-3/8"
	17-3/8"	17-3/8"
	21-3/8"	21-3/8"
Voltage Single Phase	115v	115v
Time of Full Rise	40 seconds	40 seconds

Specifications subject to change without notice or liability.



Forward Lift
996 Industrial Drive
Madison, IN 47250

Phone: 800.423.1722
Fax: 812.273.7329
www.forwardlift.com



Lit# Forward Low&Mid-Rise_2011.07

©2011 Vehicle Service Group™
Printed in the U.S.A. All rights reserved. Unless otherwise indicated,
Forward Lift, Vehicle Service Group™, Dover and all other trademarks
are property of Dover Corporation and its affiliates.